



X42

AQUA PROOF

WATERPROOFER/FABRIC PROTECTOR
5 LITRE



**PLEASE READ INSTRUCTIONS PRIOR TO USE.
SUITABLE FOR WEATHERED CANVAS ONLY.**



WARNING

KEEP OUT OF REACH OF CHILDREN

IF SWALLOWED or directly contacts face, seek medical advice. DO NOT USE in confined areas as vapours may be harmful. AVOID inhaling vapours. CONTINUE to provide ventilation until the treated article is dry. KEEP vapours away from flame and heat. KEEP children & pets away from treatment area until article is dry. DO NOT smoke or leave lit cigarettes near proofing agent or treated articles. KEEP proofing agent away from furniture & carpet.

IMPORTANT: Test a small area first to check that the product does not cause excess discolouration. This may occur on fabrics with non-fast dye. Discontinue use if this occurs. Allow minimum 12 hours for test patch to dry before continuing.

AQUA PROOF: is a fluoro chemical protective proofing agent and mould preventer and will not cause significant discolouration, stiffness or whitening of fabrics if used according to directions.

NOTE: THIS PRODUCT MAY CAUSE DAMAGE OR LOSS IF NOT USED IN STRICT ACCORDANCE WITH DIRECTIONS. FOR USE ON WEATHERED CANVAS ONLY.

CHECK WITH PLACE OF PURCHASE IF THIS PRODUCT IS SUITABLE FOR YOUR REQUIREMENTS. DO NOT PROCEED IF UNSURE AND SEEK FURTHER ADVICE.

This product is sold only subject to these conditions and upon the basis that it is used solely at the purchaser's own risk and the manufacturers hereby exclude themselves from all liability to this product however arising.

FOR USE ON:

- Camping gear (including canvas & nylon tents).
- Canvas tarpaulins and similar products.
- Outdoor furniture, umbrellas, curtains.

COVERAGE:

- Covers approximately 6 square metres per litre.

DIRECTIONS:

- **SHAKE BOTTLE WELL BEFORE USE**
- **DO NOT** spray on article to be treated (use a paint brush).

- **DO NOT** dilute product prior to application.
- Ensure the canvas is dry prior to application.
- **DO NOT** attempt to apply this product to wet canvas.
- Apply to surface evenly in a smooth, sweeping motion, ensuring a thin layer is applied.
- Do not saturate the canvas surface when applying.
- Allow the first coat to dry for a minimum of 12 hours under good conditions (i.e. greater than 20°C and less than 50% humidity).
- If the temperature is lower or humidity higher, the drying process will be extended.
- For old or worn canvas, a second coat may need to be applied, paying particular attention to areas that suffer from creasing and folding.
- Before applying second coat, test if canvas has been sealed by sprinkling a small amount of water on the surface. If water beads are created a second coat is not required.
- Until the film is completely dry the canvas should not be exposed to any form of moisture (i.e. rain, snow or condensation).
- Once completed, store canvas in a dry, cool place.
- If treated canvas is not used for a long period of time, (eg. 1 year) proofing agent may need to be applied again.

CLEANING:

- Clean brush with warm water.
- If after application, a white film appears on treated article, wash surface with warm soapy water (using a mild detergent) or warm water mixed with a small amount of white vinegar to remove.



Distributed by
Primus Australia Pty Ltd
Bundoora Victoria 3083
Customer Service: 1300 555 197