



Smarttek
Lite Smart Hot Water System

~~\$299.00~~ **\$259.00**

Details

Simple to set up and use, the reliable Smarttek Lite from provides instant hot water from a small and light unit and is ideal for compact camp or caravan setups in warmer climates. The smaller heat exchanger and burners won't raise the water temperature as far above ambient than its bigger sibling but saves a little on packed size and weight. This sleek design is just 30cm x 37 cm, weighs 4.5kg and has been tested over 12,000 cycles to ensure durability. To set it up and use it, hang it by the mounting brackets or handle, connect the gas bottle using the gas regulated hose, connect the shower rose and rose to the water outlet valve, connect the water source to the water inlet valve, insert the two included batteries provided - and you're all set for hot water out in the field. This unit provides 4.3L per minute of constant water flow with the included pump and up to 6L per minute maximum with an optional larger volume pump, has an LCD temperature display for setting the temperature, a 2 pressure setting shower head with twist on/off control, and a stainless-steel finish so it can hold up in the harsh Aussie climate. When you need dependable and portable hot water, the Smarttek Lite from Smarttek is the perfect entry-level option. Easy to set up and use
Up to 4.3L of water flow per minute with the included pump
Unit is capable of a maximum of 6l per minute with larger pumps
Stainless steel finish with stainless steel screws and double powder coated rear housing
Dust, wind, rain and shock resistant
LCD temperature display
Showerhead with 2 pressure settings and twist on/off control on the shower head
Battery powered ignition
Inbuilt energy saving function
Temperature safety cut-off switch to prevent scolding
Technical support available from 9am-7pm 7 days per week - 1300 119 906

Specifications

Snowys Code:	144729
Supplier Code:	SMA-LTE
External Dimensions:	30L x 15W x 37H cm
Packed Dimensions:	30L x 15W x 37H cm
Shower Hose Length:	2 Metres Stainless Steel Hose
Pump Hose Length:	2m 8mm Suction to pump 2m 8mm Outlet from pump 1/2" BSP fitting
Cable Length:	2.5 Metres with On/Off Switch & Two Alligator Clamps
Material:	Heater: Stainless Steel, High Grade Stainless Steel Screws and Double Powder Coated Rear Housing Pump: Metal Shell & Corrosion resistant ABS
Pump:	4.3 L/pm 12V DC Pumps up to 10m with maximum 3m rise
Fuel Type:	LPG Propane
Fuel Consumption:	Winter Mode: 28 Mj/h Summer Mode: 9Mj/h
Ignition:	Automatic
Gas Fitting to Appliance:	3/8" SAE 1200mm Regulated Hose Included
Gas Fitting to Bottle:	POL
Input Power:	12V DC
Batteries:	2 x D Cell for Ignition (Included)
Run Time:	Summer Mode: 50 Hours from a 9 Kg LPG Bottle Winter Mode: 16 Hours from a 9 Kg LPG Bottle
Max. Heat Output:	Just under 35°C above ambient (Min water, Max Gas, Winter Mode) 55°C Maximum
Flow Rate:	Up to 4.3 L/pm with included pump Up to 6L/pm maximum with optional larger volume pump Min. flow 2L/pm
Water Pressure:	Min: 25kPa – 3.63 psi Max: 750kPa – 108 psi
Weight:	4.5 Kg
Warranty:	1 Year Manufacturers Warranty Additional 2 Year Optional

Have a question about this product?

 1300 914 007  service@snowys.com.au  Snowys Outdoors  Snowys Outdoors

Changed your mind?

For all information on how to return an item, visit www.snowys.com.au/returns